



Form A - EN 175301-803 (DIN43650) / ISO 4400

Product description		EN175301-803	EN175301-803
Standard		EN175301-803	EN175301-803
Construction type		A	A
Description		P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and protective circuit (diode)	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and protective circuit (diode)
Housing colour		transparent	transparent
Number of contacts		2+PE	2+PE
Order no.		<b>KA132D54T9</b>	<b>KA132D54T1</b>
Other options on request	led colour red led colour green	order no. <b>KA132D57T9</b> order no. <b>KA132D5AT9</b>	order no. <b>KA132D57T1</b> order no. <b>KA132D5AT1</b>
Cable gland		PG9 (M16x1,5 on request)	PG11
Max. conductor size		1,5mm <sup>2</sup> without splice/terminal	1,5mm <sup>2</sup> without splice/terminal
<b>Drawing</b>			
<b>Technical data</b>			
Pin dimension		6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm
Voltage		24 V DC	24 V DC
Rated current max.		4 A	4 A
Suppressor		Diode 1A 1000V	Diode 1A 1000V
LED colour		yellow	yellow
Contact resistance		15mΩ max.	15mΩ max.
Overvoltage category		III	III
Type of termination		screw M3	screw M3
Contact screw torque		max. 0,5 N/m	max. 0,5 N/m
Suitable cables		5 mm to 7 mm diameter	6 mm to 9 mm diameter
Mounting		central screw M3x32,5	central screw M3x32,5
<b>Material</b>			
Contact material		CuSn silver plated	CuSn silver plated
Contact holder material		PA6 GF	PA6 GF
Housing material		PA12	PA12
<b>Environmental conditions</b>			
Protection class (EN 60529)		IP 65 when correctly assembled	IP 65 when correctly assembled
Pollution severity (EN 60664-1)		3	3
Temperature range		-20°C to + 80°C	-20°C to + 80°C
<b>Inflammability class</b>			
Contact holder		HB - UL 94	HB - UL 94
Housing		HB - UL 94	HB - UL 94
<b>Packaging</b>			
Packaging unit / Weight approx.		100 pieces / 2,5Kg	100 pieces / 2,5Kg
Box dimensions		29 x 15 x 18 cm	29 x 15 x 18 cm
<b>Other accessories options</b>			
to be ordered separately see pages 177-181		NBR flat gasket 100 pcs in bag Silicon profile gasket 100 pcs in bag Stainless steel screw 100 pcs in bag	NBR flat gasket 100 pcs in bag Silicon profile gasket 100 pcs in bag Stainless steel screw 100 pcs in bag

## Valve Connectors KA1 series

SELF - ASSEMBLY CABLE



EN175301-803	EN175301-803	EN175301-803	EN175301-803
A	A	A	A
P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and TVS protective circuit (transil)	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and TVS protective circuit (transil)	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and RC protective circuit	P18 connector with screw terminals NBR profile gasket (PE) earth position H12 function indicator (LED) and RC protective circuit
transparent	transparent	transparent	transparent
2+PE	2+PE	2+PE	2+PE
<b>KA132T54T9</b>	<b>KA132T54T1</b>	<b>KA132C54T9</b>	<b>KA132C54T1</b>
order no. <b>KA132T57T9</b>	order no. <b>KA132T57T1</b>		
order no. <b>KA132T5AT9</b>	order no. <b>KA132T5AT1</b>		
PG9 (M16x1,5 on request)	PG11	PG9 (M16x1,5 on request)	PG11
1,5mm <sup>2</sup> without splice/terminal	1,5mm <sup>2</sup> without splice/terminal	1,5mm <sup>2</sup> without splice/terminal	1,5mm <sup>2</sup> without splice/terminal
6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm	6,3 x 0,8mm ; 4,8 x 0,8mm
24 V AC/DC	24 V AC/DC	24 V AC/DC	24 V AC/DC
4 A	4 A	4 A	4 A
TVS Vbr max.=37,8V Peak=400W	TVS Vbr max.=37,8V Peak=400W	Filter RC C=0,1 µF R=100 Ω	Filter RC C=0,1 µF R=100 Ω
yellow	yellow	yellow	yellow
15mΩ max.	15mΩ max.	15mΩ max.	15mΩ max.
III	III	III	III
screw M3	screw M3	screw M3	screw M3
max. 0,5 N/m	max. 0,5 N/m	max. 0,5 N/m	max. 0,5 N/m
5 mm to 7 mm diameter	6 mm to 9 mm diameter	5 mm to 7 mm diameter	6 mm to 9 mm diameter
central screw M3x32,5	central screw M3x32,5	central screw M3x32,5	central screw M3x32,5
CuSn silver plated	CuSn silver plated	CuSn silver plated	CuSn silver plated
PA6 GF	PA6 GF	PA6 GF	PA6 GF
PA12	PA12	PA12	PA12
IP 65 when correctly assembled	IP 65 when correctly assembled	IP 65 when correctly assembled	IP 65 when correctly assembled
3	3	3	3
-20°C to + 80°C	-20°C to + 80°C	-20°C to + 80°C	-20°C to + 80°C
HB - UL 94	HB - UL 94	HB - UL 94	HB - UL 94
HB - UL 94	HB - UL 94	HB - UL 94	HB - UL 94
100 pieces / 2,5Kg	100 pieces / 2,5Kg	100 pieces / 2,5Kg	100 pieces / 2,5Kg
29 x 15 x 18 cm	29 x 15 x 18 cm	29 x 15 x 18 cm	29 x 15 x 18 cm
NBR flat gasket 100 pcs in bag	NBR flat gasket 100 pcs in bag	NBR flat gasket 100 pcs in bag	NBR flat gasket 100 pcs in bag
Silicon profile gasket 100 pcs in bag	Silicon profile gasket 100 pcs in bag	Silicon profile gasket 100 pcs in bag	Silicon profile gasket 100 pcs in bag
Stainless steel screw 100 pcs in bag	Stainless steel screw 100 pcs in bag	Stainless steel screw 100 pcs in bag	Stainless steel screw 100 pcs in bag

Form A - EN 175301-803 (DIN43650) / ISO 4400